

Information				ſ		Two-ear Clip - A20R INOX W4					
	Ø Appl min.	ication max.	Reference W4	A	В	C	D	E	Box Quantity	Packing	Colour
The use of Two-ear clips is an	5	7	23012108	7,3	4,3	6,0	11,5	0,6	2000	16000	INOX
economical solution for many simple	7	9	23012116	9,3	4,8	6,0	14,5	0,8	1000	16000	INOX
hose assemblies, used with air or	9	11	23012124	11,3	5,3	6,5	16,5	0,8	1000	8000	INOX
other fluids. The two ears give the	11	13	23012132	13,3	5,8	6,5	19,0	0,8	500	8000	INOX
clip extra grip and help to maintain	13	15	23012140	15,3	6,3	7,0	21,5	1,0	500	4000	INOX
constant pressure around the hose.	14	17	23012159	17,5	6,6	7,0	24,0	1,0	500	4000	INOX
itting is more flexible and exact.	15	18	23012167	18,5	7,0	7,5	25,0	1,0	500	4000	INOX
The practical design of Two-ear clips	17	20	23012175	20,5	7,6	7,5	27,0	1,0	250	2000	INOX
means that they clamp firmly on to	18	21	23012183	21,5	7,9	8,0	28,5	1,0	250	2000	INOX
he assembly and cannot be	20	23	23012191	23,5	8,5	8,0	30,5	1,0	250	2000	INOX
removed once mounted. The edges are rounded to avoid damage to the hose Due to the AISI-304 steel used in the manufacture of these clips, their corrosion resistance is outstanding. They are recommended especially in outdoor applications.	22	25	23012204	25,5	9,1	8,5	33,5	1,2	200	1600	INOX

* Please see pages 68 and 69 for further information regarding application tools.

