




W2

9mm L-band Worm-drive Hose clip

DIN: 3017 Light series



Asfa-L W2 Hose Clip (9 mm bandwidth)

Information

Thanks to the exclusive design of the housing, the ASFA-L W2 hose clip has excellent performance while being at the same time very compact. The cold-formed stamped band thread, smoothed on the underside, combined with beveled band-edges protects the hose from damage. The AISI-430 Stainless steel finish of the band and housing make this a very attractive clip. The ASFA-L W2 hose clip complies fully with the DIN 3017 norm and also with the RoHS directive EU 20032/95/EC dated 1st July 2006. This clip is very popular in the hardware and domestic markets and in automotive applications.

Ø Application mm	Reference W2	L max.	s + 0,1 0	h max.	a ± 0,3 0,2	b max.	Max. Values* Torque Nm	Max. Values* Pressure (Bars)	Box Quantity	Packing
8-12	03016508	18,0	0,6	9,5	7,5	11,5	1,5	40	200	1600
8-16	03016516	22,1	0,6	10	9	14	3,0	45	200	800
12-22	03016524	22,1	0,6	10	9	14	3,0	45	200	800
16-27	03016532	23,6	0,7	10	9	14	3,5	42	200	800
20-32	03016540	23,6	0,7	10	9	14	3,5	36	200	800
25-40	03016559	25,6	0,7	10	9	14	4,0	32	100	800
30-45	03016567	25,6	0,7	10	9	14	4,0	28	100	800
32-50	03016575	25,6	0,7	10	9	14	4,0	24	100	800
40-60	03016583	25,6	0,7	10	9	14	4,0	19	100	400
50-70	03016591	26,6	0,7	10	9	14	4,0	17	100	100
60-80	03016604	26,6	0,7	10	9	14	4,0	15	100	100
70-90	03016612	26,6	0,7	10	9	14	4,0	13	50	400
80-100	03016620	26,6	0,7	10	9	14	4,0	11	50	400
90-110	03016639	26,6	0,7	10	9	14	4,0	10	25	200
100-120	03016647	26,6	0,7	10	9	14	4,0	9	25	200
110-130	03016655	26,6	0,7	10	9	14	4,0	8	25	25
120-140	03016663	26,6	0,7	10	9	14	4,0	7	25	25
130-150	03016671	26,6	0,7	10	9	14	4,0	6	25	25
140-160	03016680	26,6	0,7	10	9	14	4,0	5	25	25

*The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

Patented Worldwide

W2 Materials

Screw:

Qst 36-3 Mild steel (DIN 1.0213)
Silver-white Cr3 Zinc-Plated

Band and Housing:

X6Cr17 Stainless steel (DIN 1.4016) (AISI-430)

