

**W3**

9mm L-band Worm-drive Hose clip

DIN: 3017 Light Series black

ASFA L Hose Clip W3 (9mm bandwidth)

Information	Ø Application mm	Reference	L max.	s + 0,1 0	h max.	a ± 0,3 0,2	b Max.	Max. Values* Torque Nm	Max. Values* Pressure (Bars)	Box Quantity	Packing
<p>Thanks to the exclusive design of the housing, the ASFA LW3 hose clip has excellent performance while being at the same time very compact. The cold-formed stamped band thread, smoothed on the underside, combined with the beveled band edges protects the hose from any damage. The ASFA-L W3 hose clip complies fully with the DIN 3017 norm and also with the RoHS directive EU 2002/95/EC dated 1st July 2006.</p> <p>The special black finish gives added corrosion resistance and makes this clip very popular in automotive and defense applications, as well as in the manufacture of agricultural machinery.</p>	8-16	73016011	22,1	0,6	10	9	14	3,0	45	200	800
	12-22	73016020	22,1	0,6	10	9	14	3,0	45	200	800
	16-27	73016038	23,6	0,7	10	9	14	3,5	42	200	800
	20-32	73016046	23,6	0,7	10	9	14	3,5	36	200	800
	25-40	73016062	25,6	0,7	10	9	14	4,0	32	100	800
	30-45	73016070	25,6	0,7	10	9	14	4,0	28	100	800
	32-50	73016089	25,6	0,7	10	9	14	4,0	24	100	800
	40-60	73016095	25,6	0,7	10	9	14	4,0	19	100	400
	50-70	73016100	26,6	0,7	10	9	14	4,0	17	100	100
	60-80	73016118	26,6	0,7	10	9	14	4,0	15	100	100

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

Patented Worldwide.

W3 Materials

Screw:
(AISI-430)
Stainless steel

Band and housing:
Stainless steel X6Cr-17
(DIN 1.4016) AISI 430

Finish:
Black

