

W1

Wire Clip with screw

Zinc-plated mild steel

AAT W1 wire clip with screw

| Information | d Ø Application mm | Application | d Ø Application nominal mm | d | e | l | h max | Box quantity | Packing |
|---|---------------------------|--------------------|-----------------------------------|----------|----------|----------|--------------|---------------------|----------------|
| This clip was specially designed for use with hoses incorporating an outer helix. It is generally used when installing ventilation ducting. The double-wire construction of this clip means that it sits comfortably on either side of the helix and can then be clamped down firmly thanks to the screw-tightening system. | 9,5-12 | 03030015 | 11,0 | 1,5 | 5,5 | 20 | 11 | 500 | 2000 |
| | 10,5-13 | 03030023 | 11,5 | 1,5 | 5,5 | 20 | 11 | 500 | 2000 |
| | 11,5-14 | 03030031 | 12,5 | 1,5 | 5,5 | 20 | 11 | 500 | 2000 |
| | 12,5-15 | 03030040 | 13,0 | 1,5 | 5,5 | 20 | 11 | 500 | 2000 |
| | 13,0-16 | 03030058 | 14,0 | 1,8 | 5,5 | 25 | 11 | 500 | 2000 |
| | 13,5-17 | 03030066 | 15,0 | 1,8 | 5,5 | 25 | 11 | 500 | 2000 |
| | 15,0-18 | 03030074 | 16,0 | 1,8 | 5,5 | 25 | 11 | 500 | 2000 |
| | 15,5-19 | 03030082 | 17,0 | 1,8 | 5,5 | 25 | 11 | 500 | 2000 |
| | 17,0-20 | 03030090 | 18,0 | 1,8 | 5,5 | 25 | 11 | 500 | 2000 |
| | 17,5-21 | 03030103 | 18,5 | 1,8 | 5,5 | 25 | 11 | 500 | 2000 |
| | 18,5-22 | 03030111 | 20,0 | 2,0 | 7,0 | 30 | 13 | 500 | 2000 |
| | 19,0-23 | 03030120 | 20,5 | 2,0 | 7,0 | 30 | 13 | 500 | 2000 |
| | 21,0-24 | 03030138 | 22,0 | 2,0 | 7,0 | 30 | 13 | 500 | 2000 |
| | 21,5-25 | 03030146 | 23,5 | 2,2 | 7,0 | 30 | 13 | 500 | 2000 |
| | 23,5-27 | 03030154 | 25,0 | 2,2 | 7,0 | 30 | 13 | 500 | 2000 |
| | 25,0-29 | 03030162 | 27,0 | 2,2 | 7,0 | 30 | 13 | 200 | 800 |
| | 27,0-31 | 03030170 | 29,0 | 2,2 | 7,0 | 30 | 13 | 200 | 800 |
| | 29,0-33 | 03030189 | 31,5 | 2,2 | 7,0 | 30 | 13 | 200 | 800 |
| | 30,5-35 | 03030197 | 33,0 | 2,2 | 7,0 | 30 | 13 | 200 | 800 |
| | 33,0-37 | 03030200 | 37,0 | 2,2 | 7,0 | 30 | 13 | 200 | 800 |
| | 35,5-40 | 03030218 | 38,5 | 2,2 | 7,0 | 30 | 13 | 200 | 800 |
| | 38,5-43 | 03030226 | 41,0 | 2,5 | 8,0 | 40 | 15 | 200 | 800 |
| | 41,0-46 | 03030234 | 43,5 | 2,5 | 8,0 | 40 | 15 | 200 | 800 |
| | 43,5-49 | 03030242 | 46,5 | 2,5 | 8,0 | 40 | 15 | 200 | 800 |
| | 46,5-53 | 03030250 | 50,5 | 2,5 | 8,0 | 40 | 15 | 100 | 400 |
| | 50,5-56 | 03030269 | 53,5 | 2,5 | 8,0 | 40 | 15 | 100 | 400 |
| | 53,5-60 | 03030277 | 56,5 | 2,8 | 10,0 | 50 | 18 | 100 | 400 |
| | 56,5-64 | 03030285 | 60,0 | 2,8 | 10,0 | 50 | 18 | 100 | 400 |
| 60,0-68 | 03030293 | 64,0 | 2,8 | 10,0 | 50 | 18 | 100 | 400 | |
| 64,0-72 | 03030306 | 68,5 | 2,8 | 10,0 | 50 | 18 | 100 | 400 | |
| 68,5-76 | 03030314 | 72,5 | 3,0 | 10,0 | 50 | 18 | 100 | 400 | |
| 72,5-80 | 03030322 | 76,5 | 3,0 | 10,0 | 50 | 18 | 100 | 400 | |
| 76,5-84 | 03030330 | 80,0 | 3,0 | 10,0 | 50 | 18 | 100 | 400 | |

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

W1 Materials

Wire:

Steel wire
B-UNI 3823

Screw:

6.6 grade steel Cr3
zinc-plated

