



- 1 **Quick close and release**
– Secure over-center lever for manual opening and closing without the need for installation tools
- 2 **Bridge**
– Optimum hose protection

Quick-release clamps

NORMACLAMP® SVS and NORMACLAMP® SVSP clamps are secure, flexible joining elements designed for applications where joints need to be closed and released frequently and quickly, such as filtering and filling systems or food industry pipeline systems that are continually being cleaned.

Advantages at a glance

- Closure can be opened and closed easily by hand
- No installation tools required

Applications

- Machine building
- Chemical industry
- Food and beverage industry
- Railway industry
- Building machines
- Pump and filter

Materials

W1	W2	W3	W4	W5
			x	

Material	Corrosion resistance in salt spray testing
W4	Min. 240 h

Technical data

Quick-release hose clamps (SVS)							
Band width	Minimum \emptyset	Maximum \emptyset	Material	Bolts			Closing force N
				W4	(0e)	Zy	
15	80	500	0.6	(•)	•	6	80
20	80	500	0.8	(•)	•	6	80
25	80	500	1.0	(•)	•	6	80

Technical data & Ordering information

NORMAFIX® SVS			
Diameter in mm	Material W4 Product No.		
	Band width		
	15 mm	20 mm	25 mm
80 - 90	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 100	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 110	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 120	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 130	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 140	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 150	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 160	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 170	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 180	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 190	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 200	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 210	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 220	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 230	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 240	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 250	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 260	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 270	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 280	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 290	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 300	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 310	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 320	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 330	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 340	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 350	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 360	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 370	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 380	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 390	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 400	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 410	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 420	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 430	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 440	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 450	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 460	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 470	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 480	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 490	0565 0154 ...	0565 0204 ...	0565 0254 ...
up to 500	0565 0154 ...	0565 0204 ...	0565 0254 ...

... = 0 without decimals in mm

SVS P



NORMACLAMP SVS clamps feature a bridge, which is ideal for clamping a hose type connection. The SVS P clamp has no bridge.

Advantages at a glance

- As it has no bridge, there is a possibility of having a profile welded onto it

Materials

- W4

NORMAFIX® SVS P			
Diameter in mm	Material W4		
	Product No.		
	Band width		
	15 mm	20 mm	25 mm
80 - 90	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 100	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 110	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 120	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 130	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 140	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 150	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 160	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 170	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 180	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 190	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 200	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 210	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 220	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 230	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 240	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 250	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 260	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 270	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 280	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 290	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 300	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 310	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 320	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 330	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 340	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 350	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 360	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 370	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 380	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 390	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 400	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 410	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 420	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 430	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 440	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 450	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 460	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 470	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 480	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 490	0566 0154 ...	0566 0204 ...	0566 0254 ...
up to 500	0566 0154 ...	0566 0204 ...	0566 0254 ...

... = 0 without decimals in mm

Eyelet bolt



If requested in the order, and assuming that an appropriate quantity is ordered, the closure can be fitted with an eyelet bolt as an alternative.

Advantages at a glance

- Eyelet bolt suitable for light duty series

Materials

- W4

NORMAFIX® SVS EYELET BOLT			
Diameter in mm	Material W4		
	Product No.		
	Band width		
	15 mm	20 mm	25 mm
80 - 90	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 100	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 110	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 120	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 130	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 140	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 150	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 160	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 170	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 180	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 190	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 200	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 210	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 220	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 230	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 240	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 250	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 260	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 270	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 280	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 290	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 300	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 310	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 320	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 330	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 340	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 350	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 360	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 370	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 380	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 390	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 400	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 410	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 420	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 430	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 440	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 450	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 460	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 470	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 480	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 490	0565 1154 ...	0565 1204 ...	0565 1254 ...
up to 500	0565 1154 ...	0565 1204 ...	0565 1254 ...

... = 0 without decimals in mm