

**W3**

# 12mm S-band Worm-drive Hose clip

**DIN: 3017 Heavy Series black**

## ASFA-S W3 Hose Clip (12mm bandwidth)

<b>Information</b>	<b>Ø Application mm</b>	<b>Reference</b>	<b>L max.</b>	<b>s + 0,1 0</b>	<b>h max.</b>	<b>a ± 0,3 0,2</b>	<b>b Max.</b>	<b>Max. Values* Torque Nm</b>	<b>Max. Values* Pressure (Bars)</b>	<b>Box Quantity</b>	<b>Packing</b>
Thanks to the exclusive design of the housing, the ASFA SW3 hose clip has excellent performance while being at the same time very compact. The cold-formed stamped band thread, smoothed on the underside, combined with the beveled band edges protects the hose from any damage. The ASFA-S W3 hose clip complies fully with the DIN 3017 norm and also with the RoHS directive EU 2002/95/EC dated 1st July 2006. The special black finish gives added corrosion resistance and makes this clip very popular in automotive and defense applications, as well as in the manufacture of agricultural machinery.	16-27	73016206	29,6	0,8	11	12,2	18	4,2	45	50	400
	20-32	73016214	29,6	0,8	11	12,2	18	5,2	45	50	400
	25-40	73016222	29,6	0,8	11	12,2	18	5,2	40	50	400
	30-45	73016230	29,6	0,8	11	12,2	18	5,2	35	50	400
	32-50	73016249	29,6	0,8	11	12,2	18	6,0	35	50	400
	40-60	73016257	29,6	0,8	11	12,2	18	6,0	30	50	400
	50-70	73016265	31,6	0,8	11	12,2	18	6,8	25	50	400
	60-80	73016273	31,6	0,8	11	12,2	18	6,8	20	50	50

\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

**Patented Worldwide.**

### W3 Materials

**Screw:**  
(AISI-430) Stainless steel

**Band and housing:**  
Stainless steel X6Cr-17  
(DIN 1.4016) AISI 430

**Finish:**  
Black

